

Database Programming with SQL

6-2 Join Clauses





Objectives

This lesson covers the following objectives:

- Construct and execute a join with the ANSI-99 USING Clause
- Construct and execute a join with the ANSI-99 ON Clause
- Construct and execute an ANSI-99 query that joins three tables



Purpose

- As you add more commands to your database vocabulary, you will be better able to design queries that return the desired result.
- The purpose of a join is to bind data together, across tables, without repeating all of the data in every table.
- Why ask for more data than you really need?



USING Clause

- In a natural join, if the tables have columns with the same names but different data types, the join causes an error.
- To avoid this situation, the join clause can be modified with a USING clause.
- The USING clause specifies the columns that should be used for the join.





USING Clause

- The query shown is an example of the USING clause.
- The columns referenced in the USING clause should not have a qualifier (table name or alias) anywhere in the SQL statement.

SELECT first_name, last_name, department_id, department_name FROM employees JOIN departments USING (department_id);

FIRST_NAME	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_NAME
Jennifer	Whalen	10	Administration
Michael	Hartstein	20	Marketing
Pat	Fay	20	Marketing
•••	•••	•••	



USING Clause

 The USING clause allows us to use WHERE to restrict rows from one or both tables:

```
SELECT first_name, last_name, department_id, department_name
FROM employees JOIN departments USING (department_id)
WHERE last_name = 'Higgins';
```

FIRST_NAME	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_NAME
Shelley	Higgins	110	Accounting

ON Clause

- What if the columns to be joined have different names, or if the join uses non-equality comparison operators such as <, >, or BETWEEN?
- We can't use USING, so instead we use an ON clause.
- This allows a greater variety of join conditions to be specified.
- The ON clause also allows us to use WHERE to restrict rows from one or both tables.



ON Clause Example

• In this example, the ON clause is used to join the employees table with the jobs table.

```
SELECT last_name, job_title
FROM employees e JOIN jobs j
ON (e.job_id = j.job_id);
```

• A join ON clause is required when the common columns have different names in the two tables.

LAST_NAME	JOB_TITLE	
King	President	
Kochhar	Administration	
KUCIIIIai	Vice President	
Dallana	Administration	
De Haan	Vice President	
Whalen	Administration	
vviiaien	Assistant	
Liggins	Accounting	
Higgins	Manager	
C: -t-	Public	
Gietz	Accountant	
Zlotkey	Sales Manager	
Abel	Sales	
Abei	Representative	
Taylor	Sales	
Taylor	Representative	





ON Clause with WHERE Clause

 Here is the same query with a WHERE clause to restrict the rows selected.

```
SELECT last_name, job_title
FROM employees e JOIN jobs j
  ON (e.job_id = j.job_id)
WHERE last_name LIKE 'H%';
```

LAST_NAME	JOB_TITLE
Higgins	Accounting Manager
Hunold	Programmer
Hartstein	Marketing Manager



ON Clause with non-equality operator

- Sometimes you may need to retrieve data from a table that has no corresponding column in another table.
- Suppose we want to know the grade_level for each employees salary.
- The job_grades table does not have a common column with the employees table.
- Using an ON clause allows us to join the two tables

job_grades table

GRADE_LEVEL	LOWEST_SAL	HIGHEST_SAL
А	1000	2999
В	3000	5999
С	6000	9999
D	10000	14999
Е	15000	24999
F	25000	40000



ON Clause with non-equality operator

```
SELECT last_name, salary, grade_level, lowest_sal, highest_sal FROM employees JOIN job_grades
ON(salary BETWEEN lowest_sal AND highest_sal);
```

LAST_NAME	SALARY	GRADE_LEVEL	LOWEST_SAL	HIGHEST_SAL
Vargas	2500	А	1000	2999
Matos	2600	А	1000	2999
Davies	3100	В	3000	5999
Rajs	3500	В	3000	5999
Lorentz	4200	В	3000	5999
Whalen	4400	В	3000	5999
Mourgos	5800	В	3000	5999
Fay	6000	С	6000	9999
•••				



Joining Three Tables

- Both USING and ON can be used to join three or more tables.
- Suppose we need a report of our employees, their department, and the city where the department is located?
- We need to join three tables: employees, departments and locations.



Joining Three Tables Example

SELECT last_name, department_name AS "Department", city
FROM employees JOIN departments USING (department_id)
 JOIN locations USING (location_id);



LAST_NAME	Department	CITY
Hartstein	Marketing	Toronto
Fay	Marketing	Toronto
Zlotkey	Sales	Oxford
Abel	Sales	Oxford
Taylor	Sales	Oxford
Hunold	IT	Southlake
Ernst	IT	Southlake
Lorentz	IT	Southlake
Mourgos	Shipping	South San Francisco

Terminology

Key terms used in this lesson included:

- ON clause
- USING clause



Summary

In this lesson, you should have learned how to:

- Construct and execute a join with the ANSI-99 USING Clause
- Construct and execute a join with the ANSI-99 ON Clause
- Construct and execute an ANSI-99 query that joins three tables

